

LM15A SERIES LED LIGHT



- The lamp series LM15A is suitable for all types of panels and enclosures, especially where durability is important
- The lamps have a very long service life thanks to the use of LED technology.
- Two different types more flexibility for installation



- LED technology
- Integrated power unit
- Magnet or screw fixing
- Long-lived and maintenance-free by

TECHNICAL DATA



Power consumption	Max. 15W
Luminous flux	1850 Lm at 120°
Lamp type	LED angle of radiation 120° Light color: daylight, color temperature: 6,500 K
Service life	50,000 h at +20 °C (+68 °F)
Connection	Terminal Connection of 3G1,5mm power cable 1,5mt (optional)
Mounting	Magnet fixing or screw fixing
Casing	Aluminium anodized profile and polycarbonate
Dimensions	365*40*40mm
Weight	0,5 kg
Operating/Storage Temperature	-40 to +60 °C (-40 to +140 °F) / -40 to +85 °C (-40 to +185 °F)
Operating/Storage Humidity	Max. 90 % RH (non-condensing)
Protection Type/Protection Class	IP20 / II (double insulated)

OrderCode Magnet Fixing

LM15-365AM
LM15-365AM-110AC
LM15-365AM-24DC
LM15-365AM-12DC

OrderCode Screw Fixing

LM15-365A
LM15-365A-110AC
LM15-365A-24DC
LM15-365A-12DC

Operating Voltage

AC 230 V, 50/60 Hz
AC 110 V, 50/60 Hz
DC 24V
DC 12V

Switch

on/off light switch
on/off light switch
on/off light switch
on/off light switch